

INDU-EYE TERMO

BATTERYLESS IOT TEMPERATURE MONITORING

INDU-EYE TERMO is a *batteryless* solution for temperature monitoring. Our device uses long-range wireless protocols and is particularly designed to be used in hard-to-reach and cost prohibitive environments.

A robust, reliable and easy-to-install *Predictive Maintenance* system allows you to remotely monitor the health of your machinery and predict the most optimal time for maintenance.

Keep your plant up

Detect proactively performance issues to reduce unplanned downtime.

Waste Heat powered

Batteryless means forgetting expensive battery maintenance and become eco-friendly.

Easy installation

Plug&Play installation without the need for cables. Long-range wireless protocols (>10 km) require very simple infrastructure compared to low-range protocols, commonly used by competitors, that need gateways or repeaters every few meters.

Monitoring dashboard

Use our DAEVIS monitoring dashboard tool or any other cloud-based system: Always choose the best settings to make your decisions.

Fully adaptable

Adaptable to any type of surface, whether flat or circular.

Flexible and scalable


It does not matter how many Indu-Eye devices you want to install and where, changing and growing your network is very easy!

Cost and environmental savings

Compared to competitors' wireless solutions (battery-powered), our products reduce the cost of devices, infrastructure, and other recurrent expenses up to 70% and more than 98% of reduction in GHG, energy, heat and water during its lifetime.

Improve your maintenance tasks

Automate routine operations keep maintenance professionals performing high-value tasks.



INDU-EYE TERMO

Wireless and Batteryless IoT Temperature Monitoring

INDU-EYE TERMO is a system consisting of three main components:

1. The industrial temperature sensor.
2. The wireless IoT device with edge computing and long-range network capabilities.
3. A thermoelectric generator, capable of powering the entire system using heat.

INDU-EYE is economical, flexible, scalable and easy to maintain and install, which means that our product is the most competitive solution on the market.



Use cases


Wireless monitoring system for early detection of faults. It permits to diagnose heating and rotating equipment, check the temperature in hazardous parts in a process and test electric motors in the following machines:

- Furnaces, Kilns and boilers.
- Pipeline, steam traps.
- Drum dryers, belt press, centrifuge decanters.
- Pumps, motors, fans, compressors, and turbines.
- Centrifugal separators, blowers, agitators, expenders, and heat exchangers.
- Thermostatic filters.

Mean features

Temperature range	-60 °C to 650 °C
Temperature accuracy	± 0.1°C to ± 1°C
Sensor type	PT100 / PT1000
Ambient temperature	-20 °C to 50 °C
Exposure temperature	50 °C to 150 °C
Communication	NB-IoT / LTE-M
Data update cycle (sample/hour)	From 1 to 10
Certifications	CE;FCC and ATEX/IECEX ongoing
Mount	Plain or pipe
Degrees of protection	IP67

Network scenario



<https://www.aeinnova.com>
info@aeinnova.com

Pare Llaurador 169, 08221
 Terrassa, BARCELONA, SPAIN
 (+34) 930 24 40 41

Represented by:

